

# ENERGY PLUS +

## ENERGY PLUS +

ENERGY PLUS+ NM is a no mix two component open-cell spray polyurethane foam insulation that can be applied in a wide range of temperatures making it suitable for a variety of climate conditions. It features consistent and quality performance with easy no mix processing, meaning less downtime and higher job site efficiency.

### Thermal Resistance

Thickness (inch)	R-Value (°F-ft <sup>2</sup> -h/Btu)
1.0	4.1
2.0	7.7
3.5	13
4.0	15



### Physical Properties

Attribute	Test	Results
Density (Nominal)	ASTM D1622	0.5 lb/ft <sup>3</sup>
Open-Cell Content (Procedure 2)	ASTM D6226	97%
Dimensional Stability (Volume Change after 7 days)	ASTM D2126	<5% @ 158°F & 97% RH
Water Vapor Transmission @ 2"	ASTM E96	9 US perms
Air Permeance	ASTM E283	0.02 L/s·m <sup>2</sup>
Re-entry (worker) Re-occupancy	ASTM D8445	1 hour 2 hours
Material Listing	Intertek	CCRR-0556
Colour	-	Cream

### Burn Characteristics

Attribute	Test	Results
Flame Spread	ASTM E84	10
Smoke Development	ASTM E84	450
Surface Burning Characteristics @ 1"	ASTM E84	Class 1 (A)
Unvented Attic Without Ignition Barrier	UVA	Walls 18" Roof 18"
Ignition Barrier (4 mils, DC 315)	AC 337 Appendix X	Walls 8" Ceiling 12"
Thermal Barrier	NFPA 286	15 min - 20 mils WFT DC 315

### Application Areas

Interior walls, attics, floors, crawlspaces, ceilings, under roof



Energy SPF

4235 Hillsboro Pike, Suite 300, Nashville, Tennessee, 37215

1-647-519-0644 | [www.energyspf.com](http://www.energyspf.com) Rev 1